

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Bituthene Primer WP-3000

MSDS ID Number: M-85768

MSDS Date: 07/13/2006

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Bituthene Primer WP-3000
MSDS Number: M-85768
Cancelled MSDS Number: M-85760
MSDS Date: 07/13/2006
Chemical Family Name: Modified Latex Dispersion
Product Use: Adhesive Surface Conditioner
Chemical Formula: Mixture-NA
CAS # (Chemical Abstracts Service Number): Mixture-NA

Manufactured by:

W.R.Grace & Co.-Conn.
62 Whittemore Avenue
Cambridge, MA 02140

Grace Canada, Inc.
294 Clements Road West
Ajax, Ontario L1S 3C6

In Case of Emergency Call:

In USA: (617) 876-1400 In Canada: (905) 683-8561

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS#	Percent (max)
Acrylic Polymer	25951-38-6	10-25
	70677-00-8	1-10
Methyl alcohol	000067-56-1	1-10

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Caution!

Causes eye irritation.
Causes skin irritation.
Causes respiratory tract irritation.
May be harmful if swallowed.

HMIS Rating:

Health: 2*
Flammability: 2
Reactivity: 0
Personal Protective Equipment: B (See Section 8)

Potential Health Effects:

Inhalation: Causes respiratory tract irritation if vapor is inhaled.
Effects include: Drowsiness, nausea, headache, dizziness.
Inhalation may also result in effects similar to those under ingestion.

Eye Contact: Eye contact causes irritation.
Prolonged eye contact can result in tissue damage.

Skin Contact: Skin contact causes irritation.
May de-fat skin.

Skin Absorption: Skin absorption of the methanol fraction of this product may cause metabolic effects similar to those outlined under ingestion.

Ingestion: If swallowed, may cause irritation to mouth, throat and stomach.
When ingested Methanol acts as a narcotic/neurotoxin and may cause mild inebriation and subsequent drowsiness, headache, weakness, vertigo, and violent pain in the back, abdomen and extremities. Effects on the eye may include blurred or dimmed vision, eye pain, partial blindness or permanent blindness may occur. Ingestion of Methanol may be fatal. Methanol poisoning may cause degenerative damage to the kidneys, liver, heart and other organs due to metabolic acidosis.

Effects include: Drowsiness, nausea, headache, dizziness and loss of consciousness.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Bituthene Primer WP-3000
MSDS ID Number: M-85768

MSDS Date: 07/13/2006

SECTION 4 - FIRST AID MEASURES:

Skin Contact: In case of skin contact, clean fingernails and wash skin with soap and water. If residue remains, clean with waterless hand-cream or abrasive soap. Never use solvents.

If discomfort or irritation persists, consult a physician.
Remove contaminated clothing and wash before reuse.

Eye Contact: Flush eyes with water for at least 15 minutes while holding eyelids open.
If discomfort or irritation persists, consult a physician.

Ingestion: Do not induce vomiting.
Never give anything by mouth to an unconscious person.
If swallowed, consult a physician immediately.

Inhalation: If symptoms develop, get fresh air. If symptoms persist, consult a physician.
If breathing has stopped, give artificial respiration then oxygen if needed.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Flash Point: >141°F
Flash Point Method: Closed Cup
Lower Explosion Limit: Not Available
Upper Explosion Limit: Not Available
Auto-ignition Temperature: Not Available

NFPA Rating:

Health: 1
Flammability: 2
Reactivity: 0

Extinguishing Media: In case of fire, use water spray, dry chemical, Carbon dioxide or foam.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion. Avoid breathing hazardous vapors or products of combustion. Keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

Unusual Fire and Explosion Hazards: None unless noted below.

SECTION 6 - ACCIDENTAL RELEASE MEASURES:

Spills/Leaks: Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures: When working around heating and air conditioning systems, block intake vents to prevent vapor from traveling into buildings. Keep away from heat, sparks and flame. Enforce no smoking policy for all trades present on job site. Keep container closed tightly when not in use to avoid unnecessary release of vapors and to prevent spills. Do not reuse empty containers.

Avoid contact with eyes, skin and clothing.

Do not take internally.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

To avoid skin contact, use gloves or barrier creams. Promptly cleanse hands with waterless hand cleaner, clean fingernails and wash with soap and water after handling.

FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE GUIDELINES (US)

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Acrylic Latex Polymer	-	-	-	-	-	-	-

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Bituthene Primer WP-3000

MSDS ID Number: M-85768

MSDS Date: 07/13/2006

Methyl alcohol	200 ppm TWA	250 ppm STEL	-	200 ppm TWA; 260 mg/m3 TWA	250 ppm STEL; 325 mg/m3 STEL	-
----------------	-------------	--------------	---	----------------------------	------------------------------	---

EXPOSURE GUIDELINES (CANADA)

Employers should consult local Provincial regulatory limits for exposure guidelines, which may vary locally.

Engineering Controls: When used in confined areas, portable ventilation equipment is recommended. Vapors are heavier than air and will build-up in confined spaces without ventilation. Vapor build-up can be life threatening. Portable equipment such as a Coppus Vano portable blower/exhauster should be used in accordance with the manufacturer's instructions.

Personal Protective Equipment:

Respiratory Protection: A chemical cartridge respirator with organic vapor cartridge and a prefilter for dusts/mists is required at or above the applicable exposure limits (Consult above Exposure Guidelines). Caution: Methanol has poor warning properties and will result in a shortened organic vapor canister service life. It is recommended that self-contained breathing apparatus (SCBA) be considered when the potential to exceed methanol exposure limits exist.

Skin Protection: PVA supported polyvinyl alcohol, nitrile or viton gloves are recommended.

Eye Protection: At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

Work/Hygienic Practices: Use good work practices to prevent vapor build-up and subsequent inhalation of vapor.

Avoid rubbing eyes while handling.

Incidental ingestion of residue on hands can be avoided by using good personal hygiene practices.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance/Odor:	Milky white, liquid with a latex paint type odor.
Odor Threshold: (ppm)	Not Determined
pH:	~7.9
Vapor Pressure: (Mm Hg)	Unknown
Vapor Density: (Air = 1)	Unknown
Solubility In Water:	Complete
Specific Gravity: (Water = 1)	~1.1
Evaporation Rate: (Butyl Acetate = 1)	Unknown
Boiling Point:	>212°F/100°C
Viscosity:	Unknown
Bulk Density: (Pounds/Cubic Foot)(Pcf)	8-12
% Volatiles: (70°F) (21°C)	~30% by weight

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions To Avoid:	Heat, Sparks, Open flames and Oxidizing materials.
Hazardous Polymerization:	Will not polymerize.
Hazardous Decomposition Products:	Carbon dioxide, Carbon monoxide and Formaldehyde.

SECTION 11 - TOXICOLOGICAL INFORMATION

<u>Ingredient(No data unless listed.)</u>	<u>CAS Number</u>	<u>LD50 and LC50</u>
Methyl alcohol	000067-56-1	Inhalation LC50 Rat: 64000 ppm/4H; Oral LD50 Rat: 5628 mg/kg; Oral LD50 Mouse: 7300 mg/kg; Dermal LD

Carcinogenicity:

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Acrylic Latex Polymer	No	No	No	No	No	No

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Bituthene Primer WP-3000
MSDS ID Number: M-85768

MSDS Date: 07/13/2006

Methyl alcohol	No	No	No	No	No	No
----------------	----	----	----	----	----	----

Mutagenicity: Not applicable.
Teratogenicity: Not applicable.
Reproductive Toxicity: Not applicable.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate: No data available for product.
Ecotoxicity: No data available for product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Procedures: Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Not Applicable
UN/NA Number: Not Applicable
Domestic Hazard Class: Non-hazardous
Surface Freight Classification: Adhesives Cement N.O.S.
Label/Placard Required: Not Applicable

SECTION 15 - REGULATORY INFORMATION

REGULATORY CHEMICAL LISTS:

CERCLA (Comprehensive Response Compensation and Liability Act):
(None present unless listed below)

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>	<u>CERCLA RQ</u>
Methyl alcohol	000067-56-1	1.3	5000 lb final RQ; 2270 kg final RQ

SARA Title III (Superfund Amendments and Reauthorization Act)

SARA Section 312/Tier I & II Hazard Categories:

Health Immediate (acute)	Yes
Health Delayed (chronic)	Yes
Flammable	No
Reactive	No
Pressure	No

302 Reportable Ingredients (Identification Threshold 1%):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>	<u>SARA 302 TPQ</u>
----------------------	--------------	-------------	---------------------

313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Ammonia	007664-41-7	.02
Methyl alcohol	000067-56-1	1.3

National Volatile Organic Compound Emission Standards For Architectural Coatings:

Volatile Organic Content: (gr/L) 93 g/L

WHMIS Classification(s): D2 B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This MSDS contains all the information required by the CPR.

State Regulatory Information:

California Proposition 65: This product does not contain substances known to the state of California to cause cancer, birth defects or other reproductive harm.

Massachusetts Hazardous Substance List(Identification threshold 0.001%(1ppm)):

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Bituthene Primer WP-3000
MSDS ID Number: M-85768

MSDS Date: 07/13/2006

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Ammonia	007664-41-7	.02

New Jersey Hazardous Substance List (Identification threshold (0.1%)):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Methyl alcohol	000067-56-1	1.3

Pennsylvania Hazardous Substance List (Identification threshold 0.01%):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
-----------------------------	---------------------	--------------------

CHEMICAL INVENTORY STATUS:

All chemicals in this product are listed or exempt from listing in the following countries:

US	CANADA		EUROPE	AUSTRALIA	JAPAN	KOREA	PHILIPPINES
TSCA	DSL	NDSL	EINECS/ELINCS	AICS	ENCS	ECL	PICCS
Yes	Yes	No	Not Determined	Not Determined	Not Determined	Not Determined	Not Determined

SECTION 16 - OTHER INFORMATION

Non-Hazardous Ingredient Disclosure:

<u>Chemical Name</u>	<u>CAS Number</u>
Water	007732-18-5

Prepared by: EH&S Department
Approved by: EH&S Department
Approved Date: 07/13/2006

Disclaimer:

"The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection."