

**DIAMOND CLEAR - 55 GAL DRUM**Version 2.  
REVISION DATE: 09/12/2008

Print Date 09/13/2008

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : DIAMOND CLEAR - 55 GAL DRUM  
Product code : 359 55

COMPANY : Euclid Chemical Company  
19218 Redwood Road  
Cleveland, OH 44110

Telephone : 1-800-321-7628  
Emergency Phone: : U.S. only: 1-800-424-9300  
International Users Call Collect: 1-703-527-3887

Product use : Sealer

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Clear. Liquid. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.

Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause moderate irritation.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Di(2-ethylhexyl) phthalate, (dioctyl phthalate) given in the diet, produced increased incidence of liver cancers in female rats and male and female mice. An increased incidence of liver cancers or neoplasms were observed in male rats. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Styrene was reported to cause liver and kidney damage in experimental animals at high

**DIAMOND CLEAR - 55 GAL DRUM**

Version 2.

Print Date 09/13/2008

REVISION DATE: 09/12/2008

levels of exposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nerve, Reproductive

**SECTION 3 - PRODUCT COMPOSITION**

| Chemical Name                         | CAS-No.                 | Weight %    |
|---------------------------------------|-------------------------|-------------|
| Aromatic petroleum distillates        | 64742-95-6              | 40.0 - 70.0 |
| 1,2,4-Trimethylbenzene                | 95-63-6                 | 15.0 - 40.0 |
| Styrene Ethylhexyl Acrylate Copolymer | NJ TSRN# 51721300-5841P | 15.0 - 40.0 |
| 1,3,5-Trimethylbenzene                | 108-67-8                | 5.0 - 10.0  |
| Diethylbenzene, Mixed Isomers         | 25340-17-4              | 1.0 - 5.0   |
| Cumene                                | 98-82-8                 | 1.0 - 5.0   |
| Dioctyl phthalate                     | 117-81-7                | 1.0 - 5.0   |
| Xylene                                | 1330-20-7               | 1.0 - 5.0   |
| Ethylbenzene                          | 100-41-4                | - <1.0      |
| Styrene                               | 100-42-5                | - <1.0      |

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

|              |   |  |
|--------------|---|--|
| Inhalation   | : | Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. |
| Eye contact  | : | Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.  |
| Skin contact | : | Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.  |
| Ingestion    | : | Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.   |

**SECTION 5 - FIRE FIGHTING MEASURES**

|                               |   |  |
|-------------------------------|---|--|
| Flash point                   | : | 114 F, 46 C  |
| Method                        | : | Setaflash Closed Cup   |
| Lower explosion limit         | : | 1.00 %(V) Solvent  |
| Upper explosion limit         | : | 7 %(V) Solvent   |
| Autoignition temperature      | : | Not available.   |
| Extinguishing media           | : | If water fog is ineffective, use carbon dioxide, dry chemical or foam.               |
| Hazardous combustion products | : | Smoke, fumes. Carbon monoxide and carbon dioxide can form. Nitrogen oxides can form. |



**DIAMOND CLEAR - 55 GAL DRUM**

Version 2.  
REVISION DATE: 09/12/2008

Print Date 09/13/2008

- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.
- Fire and explosion conditions : Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

| <u>Chemical Name</u>   | <u>CAS Number</u> | <u>Regulation</u> | <u>Limit</u> | <u>Form</u> |
|------------------------|-------------------|-------------------|--------------|-------------|
| 1,2,4-Trimethylbenzene | 95-63-6           | ACGIH TWA:        | 25 ppm       |             |

**DIAMOND CLEAR - 55 GAL DRUM**

Version 2.

Print Date 09/13/2008

REVISION DATE: 09/12/2008

| <b>Chemical Name</b>   | <b>CAS Number</b> | <b>Regulation</b>                      | <b>Limit</b>                    | <b>Form</b> |
|------------------------|-------------------|--|---------------------------------|-------------|
| 1,3,5-Trimethylbenzene | 108-67-8          | ACGIH TWA:                             | 25 ppm                          |             |
| Cumene                 | 98-82-8           | ACGIH TWA:<br>OSHA PEL:                | 50 ppm<br>245 mg/m3             |             |
| Diocetyl phthalate     | 117-81-7          | ACGIH TWA:<br>OSHA PEL:                | 5 mg/m3<br>5 mg/m3              |             |
| Xylene                 | 1330-20-7         | ACGIH TWA:<br>ACGIH STEL:<br>OSHA PEL: | 100 ppm<br>150 ppm<br>435 mg/m3 |             |
| Ethylbenzene           | 100-41-4          | ACGIH TWA:<br>ACGIH STEL:<br>OSHA PEL: | 100 ppm<br>125 ppm<br>435 mg/m3 |             |
| Styrene                | 100-42-5          | ACGIH TWA:<br>ACGIH STEL:<br>OSHA TWA: | 20 ppm<br>40 ppm<br>100 ppm     |             |

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                              |
|---------------------|------------------------------|
| Form                | : Liquid                     |
| Color               | : Clear                      |
| Odor                | : Aromatic Solvent           |
| pH                  | : Not available.             |
| Vapour pressure     | : 9.5 hPa at 70 °F           |
| Vapor density       | : Heavier than air           |
| Melting point/range | : Not available.             |
| Freezing point      | : Not available.             |
| Boiling point/range | : 320 - 335 °F, 160 - 168 °C |
| Water solubility    | : Negligible                 |
| Specific Gravity    | : 0.895                      |
| % Volatile Weight   | : 77.3 %                     |

**SECTION 10 - REACTIVITY / STABILITY**

|                          |   |
|--------------------------|---|
| Substances to avoid      | : Oxidizing agents.Strong acids.Strong bases.   |
| Stability                | : Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources. |
| Hazardous polymerization | : Will not occur.   |



**DIAMOND CLEAR - 55 GAL DRUM**

Version 2.  
REVISION DATE: 09/12/2008

Print Date 09/13/2008

**SECTION 11 - TOXICOLOGICAL INFORMATION**

|                                      |  |
|--------------------------------------|--|
| Cumene, CAS-No.: 98-82-8             |  |
| Acute oral toxicity (LD-50 oral)     | 2,910 mg/kg ( Rat ) 1,400 mg/kg ( Rat )  |
| Acute inhalation toxicity (LC-50)    | 2,000 mg/l for 7 h ( Mouse ) 8,000 mg/l for 4 h ( Rat ) 24.7 mg/l for 2 h ( Mouse )                                  |
| <br>                                 |  |
| Dioctyl phthalate, CAS-No.: 117-81-7 |  |
| Acute oral toxicity (LD-50 oral)     | 25,000 mg/kg ( Rat ) 25,000 mg/kg ( Rat ) 30,000 mg/kg ( Mouse ) 33,900 mg/kg ( Rabbit ) 26,300 mg/kg ( Guinea pig ) |
| Acute dermal toxicity (LD-50 dermal) | 25,000 mg/kg ( Rabbit ) 10,000 mg/kg ( Guinea pig ) 25,000 mg/kg ( Rabbit )  |
| <br>                                 |  |
| Xylene, CAS-No.: 1330-20-7           |  |
| Acute oral toxicity (LD-50 oral)     | 4,300 mg/kg ( Rat ) 1,590 mg/kg ( Mouse ) 6,670 mg/kg ( Rat ) 3,523 - 8,600 mg/kg ( Rat ) 5,627 mg/kg ( Mouse )      |
| Acute inhalation toxicity (LC-50)    | 6,350 mg/l for 4 h ( Rat ) 3,907 mg/l for 6 h ( Mouse ) 8,000 mg/l for 4 h ( Rat )                                   |
| <br>                                 |  |
| Ethylbenzene, CAS-No.: 100-41-4      |  |
| Acute oral toxicity (LD-50 oral)     | 5,460 mg/kg ( Rat ) 3,500 mg/kg ( Rat )  |
| Acute dermal toxicity (LD-50 dermal) | 17,800 mg/kg ( Rabbit )  |
| <br>                                 |  |
| Styrene, CAS-No.: 100-42-5           |  |
| Acute oral toxicity (LD-50 oral)     | 5,000 mg/kg ( Rat ) 1,000 mg/kg ( Rat ) 316 mg/kg ( Mouse )  |
| Acute inhalation toxicity (LC-50)    | 4,940 mg/l for 2 h ( Mouse ) 2,770 mg/l for 4 h ( Rat ) 24 mg/l for 4 h ( Rat )                                      |

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)  
This classification applies only to the material as it was originally produced.

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
NOT REGULATED

**DIAMOND CLEAR - 55 GAL DRUM**Version 2.  
REVISION DATE: 09/12/2008

Print Date 09/13/2008

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

|                     |   |                        |           |
|---------------------|---|------------------------|-----------|
| SARA 313 Components | : | 1,2,4-Trimethylbenzene | 95-63-6   |
|                     |   | Cumene                 | 98-82-8   |
|                     |   | Diethyl phthalate      | 117-81-7  |
|                     |   | Xylene                 | 1330-20-7 |
|                     |   | Ethylbenzene           | 100-41-4  |
|                     |   | Styrene                | 100-42-5  |

|                      |   |                     |
|----------------------|---|---------------------|
| SARA 311/312 Hazards | : | Acute Health Hazard |
|                      |   | Fire Hazard         |

**OSHA Hazardous Components :**

|                        |           |
|------------------------|-----------|
| 1,2,4-Trimethylbenzene | 95-63-6   |
| 1,3,5-Trimethylbenzene | 108-67-8  |
| Cumene                 | 98-82-8   |
| Diethyl phthalate      | 117-81-7  |
| Xylene                 | 1330-20-7 |
| Ethylbenzene           | 100-41-4  |
| Styrene                | 100-42-5  |

|  |   |          |
|--|---|----------|
| OSHA Status: Considered hazardous based on the following criteria: | : | Irritant |
|--|---|----------|

|                   |   |    |
|-------------------|---|----|
| OSHA Flammability | : | II |
|-------------------|---|----|

|  |   |                 |
|--|---|-----------------|
| Regulatory VOC (less water and exempt solvent) | : | 700 g/l 692 g/l |
| VOC Method 310                                 | : | 77 %            |

**U.S. State Regulations:**

|                     |   |                        |           |
|---------------------|---|------------------------|-----------|
| MASS RTK Components | : | 1,2,4-Trimethylbenzene | 95-63-6   |
|                     |   | 1,3,5-Trimethylbenzene | 108-67-8  |
|                     |   | Cumene                 | 98-82-8   |
|                     |   | Diethyl phthalate      | 117-81-7  |
|                     |   | Xylene                 | 1330-20-7 |

|                     |   |                                       |                         |
|---------------------|---|---------------------------------------|-------------------------|
| Penn RTK Components | : | Aromatic petroleum distillates        | 64742-95-6              |
|                     |   | 1,2,4-Trimethylbenzene                | 95-63-6                 |
|                     |   | Styrene Ethylhexyl Acrylate Copolymer | NJ TSRN# 51721300-5841P |
|                     |   | 1,3,5-Trimethylbenzene                | 108-67-8                |
|                     |   | Cumene                                | 98-82-8                 |
|                     |   | Diethyl phthalate                     | 117-81-7                |
|                     |   | Xylene                                | 1330-20-7               |



**DIAMOND CLEAR - 55 GAL DRUM**

Version 2.

Print Date 09/13/2008

REVISION DATE: 09/12/2008

|                   |   |  |
|-------------------|---|--|
| NJ RTK Components | : Aromatic petroleum distillates<br>1,2,4-Trimethylbenzene<br>Styrene Ethylhexyl Acrylate<br>Copolymer<br>1,3,5-Trimethylbenzene<br>Diethylbenzene, Mixed Isomers<br>Cumene<br>Xylene | 64742-95-6<br>95-63-6<br>NJ TSRN# 51721300-5841P<br><br>108-67-8<br>25340-17-4<br>98-82-8<br>1330-20-7 |
|-------------------|---|--|

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

|          |                    |
|----------|--------------------|
| 117-81-7 | Diocetyl phthalate |
| 100-41-4 | Ethylbenzene       |

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

|              |   |
|--------------|---|
| Health       | 2 |
| Flammability | 2 |
| Reactivity   | 0 |
| PPE          |   |

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration

- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System