




# Material Safety Data Sheet

MINERAL SURFACED CAP SHEET  
 ASPHALT SATURATED ORGANIC FELTS  
 ASPHALT SATURATED ORGANIC BASE SHEETS  
 ASPHALT SATURATED FIBERGLASS PLY SHEETS  
 ASPHALT SATURATED FIBERGLASS BASE SHEETS  
 ORGANIC MINERAL SURFACE ROLL ROOFING



**Manufacturer:**  
 TARCO  
 One Information Way, Suite 225, Little Rock, AR 72202  
**Phone Number:** (For Information): 501-945-4506  
**Emergency Phone Number:** 254-939-3775

**Identity:** Trade name as used on label  
**MSDS Number:** 0106  
**CAS Number:** NONE  
**Date Prepared:** 8-31-01, Revised:  
**Prepared By:** D. RAINS

## SECTION 1 – MATERIAL IDENTIFICATION AND INFORMATION

	Cas Reg. #	%	OSHA TWA	ACGIH TWA	FORM
Petroleum Asphalt Flux	8052-42-4	< 60	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>	Fume
Limestone	1317-65-3	20 - 60	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>	Respirable Particulate
Sand	14808-60-7	< 20	.1mg/m <sup>3</sup>	.05mg/m <sup>3</sup>	Respirable Particulate
Organic Felt	NE	40 - 60	NE	NE	NE
Fiberglass	65997-17-3	< 5	5mg/m <sup>3</sup>	10mg/m <sup>3</sup>	Respirable Particulate
Granules	NE	< 50	NE	NE	

NE=Not Established

## SECTION 2 PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	> 650°F	Specific Gravity (H2O = 1)	N/A
Vapor Pressure (mm Hg and Temperature)	N/A	Melting Point	> 200°F
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	INSOLUBLE	Water Reactive	N/A

### Odor and Appearance

SMALL AMOUNT OF ASPHALTIC ODOR ASSOCIATED WITH ALL TARCO ROOFING PRODUCTS.  
 MINERAL SURFACED CAPSHEET: MEMBRANE ROLL WITH MINERAL AND SAND SURFACES  
 ASPHALT SATURATED ORGANIC FELT AND BASE SHEETS: BLACK MEMBRANE ROLL  
 ASPHALT SATURATED FIBERGLASS BASE AND PLY SHEETS: BLACK MEMBRANE ROLL

## SECTION 3 – FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method Used 500°F, COC	Auto-Ignition Temperature 750° F	Flammability Limits in Air % by Volume N/A	LEL N/A	UEL N/A
---	-------------------------------------	---	------------	------------

**Extinguisher Media:** FOAM, CO2, DRY CHEMICAL, HALON – AVOID USE OF STRAIGHT STREAM WATER

**Special Fire Fighting Procedures:** WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING

**Unusual Fire and Explosion Hazards:** WHEN HEATED, FUMES MAY BURN IF AN IGNITION SOURCE IS PROVIDED. FUMES MAY EXPLODE IF EMITTED IN AN ENCLOSED ENVIRONMENT WITH AN IGNITION SOURCE.

