

**HEY'DI SEALING LIQUID 1GL/6PK**

Version 1.

Print Date 07/13/2007

REVISION DATE: 12/12/2006

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : HEY'DI SEALING LIQUID 1GL/6PK  
 Product code : TL1943501

COMPANY : Euclid Chemical Company  
 19218 Redwood Road  
 Cleveland, OH 44110

Telephone : 1-800-321-7628  
 Emergency Phone: : U.S. only: 1-800-255-3924  
 International Users Call Collect: 1-813-248-0585

Product use : Coating

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Clear. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : No serious effects anticipated under normal conditions of use.  
 Eyes : Direct contact may cause mild irritation.  
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : May cause mild irritation.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged or repeated exposure to vapors of isopropyl alcohol can cause eye, skin, or respiratory irritation, headache, dizziness, nausea, in coordination, drowsiness, and loss of consciousness. Prolonged or repeat exposure to liquid can cause defatting, drying, and irritation of the skin dermatitis. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	> 60.0
Potassium sodium aluminosilicate	12736-96-8	15.0 - 40.0
Sodium silicate	1344-09-8	5.0 - 10.0
2-Propanol	67-63-0	1.0 - 5.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

**HEY'DI SEALING LIQUID 1GL/6PK**

Version 1.

Print Date 07/13/2007

REVISION DATE: 12/12/2006

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Get medical attention. Do not induce vomiting.
Notes to physician	:	Not applicable.

**SECTION 5 - FIRE FIGHTING MEASURES**

Flash point	:	> 100 °C, > 212 °F
Method	:	Not available.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

**SECTION 7 - HANDLING AND STORAGE**

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protection equipment**



**HEY'DI SEALING LIQUID 1GL/6PK**

Version 1.  
REVISION DATE: 12/12/2006

Print Date 07/13/2007

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
2-Propanol	67-63-0	ACGIH TWA: ACGIH STEL: OSHA PEL:	200 ppm 400 ppm 980 mg/m3	

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquid
- Color : Clear
- Odor : None
- pH : 9 - 11
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : 32 °F, 0 °C
- Boiling point/range : 212 °F, 100 °C
- Water solubility : Soluble
- Specific Gravity : 1.1
- % Volatile Weight : 76.4 %

**SECTION 10 - REACTIVITY / STABILITY**

- Substances to avoid : Strong acids. Strong bases.
- Stability : Stable

**HEY'DI SEALING LIQUID 1GL/6PK**

Version 1.

Print Date 07/13/2007

REVISION DATE: 12/12/2006

Hazardous polymerization : Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Sodium silicate, CAS-No.: 1344-09-8  
 Acute oral toxicity (LD-50 oral) 1,100 - 1,600 mg/kg ( Rat ) 1,100 mg/kg ( Mouse )

2-Propanol, CAS-No.: 67-63-0  
 Acute oral toxicity (LD-50 oral) 4,700 - 5,800 mg/kg ( Rat )  
 Acute dermal toxicity (LD-50 dermal) 5,030 - 7,900 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA****TDG / DOT Shipping Description:**

NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :  
 2-Propanol 67-63-0

OSHA Status: Considered : Irritant  
 hazardous based on the  
 following criteria:

OSHA Flammability : IIIB



**HEY'DI SEALING LIQUID 1GL/6PK**

Version 1.

Print Date 07/13/2007

REVISION DATE: 12/12/2006

Regulatory VOC (less water and exempt solvent) : 88 g/l  
 VOC Method 310 : 1 %

**U.S. State Regulations:**

MASS RTK Components : 2-Propanol 67-63-0

Penn RTK Components : Water 7732-18-5  
 Potassium sodium aluminosilicate 12736-96-8  
 Sodium silicate 1344-09-8  
 2-Propanol 67-63-0

NJ RTK Components : Water 7732-18-5  
 Potassium sodium aluminosilicate 12736-96-8  
 Sodium silicate 1344-09-8  
 2-Propanol 67-63-0

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:  
 None known.

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	1
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT - Department of Transportation  
 DSL - Domestic Substance List  
 EPA - Environmental Protection Agency  
 HMIS - Hazardous Materials Information System  
 IARC - International Agency for Research on Cancer  
 MSHA - Mine Safety Health Administration  
 NDSL - Non-Domestic Substance List  
 NIOSH - National Institute for Occupational Safety and Health  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 RTK - Right To Know  
 SARA - Superfund Amendments and Reauthorization Act  
 STEL - Short Term Exposure Limit  
 TLV - Threshold Limit Value  
 TSCA - Toxic Substances Control Act  
 TWA - Time Weighted Average  
 V - Volume  
 VOC - Volatile Organic Compound  
 WHMIS - Workplace Hazardous Materials Information System