

MATERIAL SAFETY DATA SHEET
Prepared according to 29 CFR 1910.1200

DATE PREPARED: January, 1995
DATE REVISED: April, 2007

PAGE 1
MSDS NO: 236

SECTION I - IDENTIFICATION

L & M CONSTRUCTION CHEMICALS, INC.
14851 CALHOUN ROAD
OMAHA, NE 68152

ID NO.: N/A

PRODUCT
NAME: **LUMISEAL FX**

DOT CLASS: Not Regulated

CHEMICAL
NAME: Acrylic Resin Emulsion

DOT SHIPPING
NAME: Resin Solution

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

INGREDIENTS	OSHA PEL	ACGIH TLV	CAS	% wt
#1: Acrylic Polymer	Not Listed	Not Listed	028377-44-8l	< 30
#2: Ester Alcohol	Not Listed	Not Listed	025265-77-4	< 5

There are no SARA 313 chemicals in this product.
Unlisted ingredients are not considered hazardous per OSHA Standard 29 CFR 1910.1200 and are considered to be trade secrets of L&M Construction Chemicals, Inc.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (F): 212
VAPOR PRESSURE (mm Hg): 24 @ 77 DEG. F.
VAPOR DENSITY (AIR = 1): 6
SOLUBILITY IN WATER: YES
APPEARANCE: Translucent liquid, dries clear
ODOR: Mild

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, °F, (TCC): N/A
FLAMMABLE LIMITS - LEL: N/A UEL: N/A

EXTINGUISHING MEDIA: Use foam, CO₂, or dry chemical fighting apparatus.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool.

SECTION V - REACTIVITY DATA

STABILITY: unstable: stable: X
INCOMPATIBILITY (materials to avoid): Avoid water reactive materials.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon monoxide and carbon dioxide if burned with insufficient air
HAZARDOUS POLYMERIZATION: may occur: will not occur: X
CONDITIONS TO AVOID: None

SECTION VI - HEALTH HAZARD DATA**LUMISEAL FX**

POTENTIAL EFFECTS OF EXPOSURE (listed by primary routes of entry)

INHALATION: Low hazard for usual industrial handling.

EYE CONTACT: May cause transient irritation. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes..

SKIN: Low hazard for usual industrial handling. Wash with soap and water if exposed to material.

INGESTION: Seek medical advise.

EMERGENCY & FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If irritation persists, seek medical attention.

SKIN: If this product comes in contact with the skin, wash with soap and large quantities of water and seek attention if irritation from contact persists.

INGESTION: If this product is swallowed, **DO NOT INDUCE VOMITING**. Seek immediate medical advice and/or attention.

EYE CONTACT: If this product comes in contact with the eyes, flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

CARCINOGENICITY OSHA: NO NTP: NO IARC: NO

SECTION VII - PRECAUTIONS FOR SAFE HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Provide adequate ventilation. Absorb and dispose of in accordance with local applicable regulations. Call emergency number if spillage poses threat to man or environment.

WASTE DISPOSAL METHOD: Dispose in accordance with local, state and federal regulations. Use qualified disposal company to incinerate at an approved facility. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: Keep containers cool, dry, and away from sources of ignition. Use and store with adequate ventilation.

OTHER PRECAUTIONS: Avoid inhalation of vapors. Avoid personal contact with the product. If contact is made, remove saturated clothing and flush affected areas with water.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. Respirator type: mist, organic vapor. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 29 CFR 1910.134.

VENTILATION

LOCAL EXHAUST: May be required in poorly ventilated spaces or evaporation from large surfaces.

SPECIAL: Required only in extreme cases. Minimize eye and skin contact.

WORK/HYGIENIC PRACTICES: Eye washes and safety showers in work area are recommended.

END OF MSDS