



# MATERIAL SAFETY DATA SHEET

Page 1 of 4

## SIKATOP 144 "A"/SIKATOP SEAL 107 "A"/SIKALATEX/SIKALATEX R

### HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

### 1. Product And Company Identification

#### Supplier

SIKA CORPORATION  
201 Polito Ave  
Lyndhurst, NJ 07071

Company Contact: Kristin Kelley  
Telephone Number: (201) 933-8800  
FAX Number: (201) 933-9379  
Web Site: www.sikausa.com

#### Manufacturer

SIKA CORPORATION  
201 Polito Ave  
Lyndhurst, NJ 07071

Company Contact: Kristin Kelley  
Telephone Number: (201) 933-8800  
FAX Number: (201) 933-9379  
Web Site: www.sikausa.com

#### Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

#### Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

Issue Date: 04/18/2001

Product Name: SIKATOP 144 "A"/SIKATOP SEAL 107 "A"/SIKALATEX/SIKALATEX R

CAS Number: Not Established

Chemical Family: ACRYLIC AQUEOUS EMULSION

MSDS Number: 2172

Product Code: 0747-130

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
ACRYLIC POLYMER	Trade Secret	

### 3. Hazards Identification

#### Eye Hazards

MAY CAUSE EYE IRRITATION.

#### Skin Hazards

MAY CAUSE SKIN IRRITATION.

#### Ingestion Hazards

MAY CAUSE STOMACH DISCOMFORT.

#### Inhalation Hazards

MAY CAUSE SLIGHT RESPIRATORY IRRITATION.

### 4. First Aid Measures

No Data Available...

## SIKATOP 144 "A"/SIKATOP SEAL 107 "A"/SIKALATEX/SIKALATEX R

### 4. First Aid Measures - Continued

#### Eye

RINSE EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.

#### Skin

WASH SKIN THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS PERSIST CONSULT PHYSICIAN.

#### Ingestion

DILUTE WITH WATER. CONSULT PHYSICIAN IF NECESSARY.

#### Inhalation

REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, INSTITUTE ARTIFICIAL RESPIRATION. CONSULT WITH PHYSICIAN.

### 5. Fire Fighting Measures

**Flash Point:** >200 °F

**Autoignition Point:** N/AV °F

#### Fire And Explosion Hazards

MATERIAL CAN SPLATTER ABOVE 100C/212F.

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

#### Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

### 6. Accidental Release Measures

WEAR SUITABLE PROTECTIVE EQUIPMENT. CONTAIN SPILL AND COLLECT WITH ABSORBENT MATERIAL AND TRANSFER INTO SUITABLE CONTAINERS. AVOID CONTACT. FLOOR MAY BE SLIPPERY; USE CARE TO AVOID FALLING.

### 7. Handling And Storage

#### Handling And Storage Precautions

STORE IN A COOL DRY AREA. KEEP CONTAINERS TIGHTLY CLOSED. AVOID FREEZING.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation.

#### Eye/Face Protection

Safety glasses with side shields or goggles.

#### Skin Protection

CHEMICAL RESISTANT RUBBER OR PLASTIC GLOVES RECOMMENDED. WEAR LONG SLEEVE SHIRT AND LONG PANTS.

#### Respiratory Protection

In areas where the P.E.L.s are exceeded, use a properly fitted NIOSH-approved respirator.

## SIKATOP 144 "A"/SIKATOP SEAL 107 "A"/SIKALATEX/SIKALATEX R

<p><b>8. Exposure Controls/Personal Protection - Continued</b></p> <p><b><u>Other/General Protection</u></b> WASH THOROUGHLY AFTER HANDLING.</p> <p><b><u>Ingredient(s) - Exposure Limits</u></b> ACRYLIC POLYMER OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED IARC: NO NTP: NO</p>
<p><b>9. Physical And Chemical Properties</b></p> <p><b><u>Appearance</u></b> MILKY WHITE LIQUID</p> <p><b><u>Odor</u></b> AMMONIA ODOR</p> <p><b>Chemical Type:</b> Pure <b>Physical State:</b> Liquid <b>Melting Point:</b> 32 °F 0 °C <b>Boiling Point:</b> 212 °F 100 °C <b>Specific Gravity:</b> 1.0-1.2 <b>Percent Volatiles:</b> 71-73water <b>Packing Density:</b> 1.0-1.2 <b>Vapor Pressure:</b> 17mm Hg at 20C water <b>Vapor Density:</b> &lt;1 WATER <b>pH Factor:</b> N/AV <b>Solubility:</b> N/AV <b>Evaporation Rate:</b> &lt; 1 WATER</p>
<p><b>10. Stability And Reactivity</b></p> <p><b>Stability:</b> STABLE <b>Hazardous Polymerization:</b> WILL NOT OCCUR</p> <p><b><u>Conditions To Avoid (Stability)</u></b> AVOID FREEZING</p> <p><b><u>Incompatible Materials</u></b> NONE KNOWN</p> <p><b><u>Hazardous Decomposition Products</u></b> NONE KNOWN</p>
<p><b>11. Toxicological Information</b></p> <p><b><u>Conditions Aggravated By Exposure</u></b> NONE KNOWN</p>
<p><b>12. Ecological Information</b></p> <p>No Data Available...</p>
<p><b>13. Disposal Considerations</b></p> <p>Dispose in accordance with applicable federal, state and local government regulations.</p>

# MATERIAL SAFETY DATA SHEET

Page 4 of 4

## SIKATOP 144 "A"/SIKATOP SEAL 107 "A"/SIKALATEX/SIKALATEX R

### 14. Transport Information

#### Proper Shipping Name

NOT REGULATED PER D.O.T.

### 15. Regulatory Information

#### U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

### 16. Other Information

#### HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

PPE: B

#### Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION