



MATERIAL SAFETY DATA SHEET

Sikadur® 42 Grout-Pak Part A

HMIS

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071 Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com	Manufacturer Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071 Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com
Supplier Emergency Contacts & Phone Number CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887	Manufacturer Emergency Contacts & Phone Number CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887

Issue Date: 05/19/2005
Product Name: Sikadur® 42 Grout-Pak Part A
CAS Number: Not Established
Chemical Family: EPOXY RESIN
MSDS Number: 3612
Product Code: 0335-13N

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON	68477-31-6	
MODIFIED EPOXY RESIN	Trade Secret	

3. Hazards Identification

Eye Hazards
Causes eye irritation.

Skin Hazards
May cause skin irritation.

Ingestion Hazards
Aspiration hazard if swallowed. Can enter lungs and cause damage.

Inhalation Hazards
May cause respiratory tract irritation.

MATERIAL SAFETY DATA SHEET

Sikadur® 42 Grout-Pak Part A

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.. Get medical attention immediately.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration.

5. Fire Fighting Measures

Flash Point: >220 °F

Flammability Class: NCMB

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Not for internal consumption. Keep containers tightly closed. Use only with adequate ventilation.

Handling Precautions

Avoid contact with eyes. Avoid contact with skin and clothing.

Storage Precautions

Store in a dry place.

Work/Hygienic Practices

Use good personal hygiene.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

MATERIAL SAFETY DATA SHEET

Sikadur® 42 Grout-Pak Part A

8. Exposure Controls/Personal Protection - Continued

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure (Long sleeve shirt and long pants). Launder before reuse.

Respiratory Protection

In case of inadequate ventilation, use NIOSH-approved respirator. A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use.

9. Physical And Chemical Properties

Appearance

STRAW COLORED LIQUID

Odor

AROMATIC ODOR

Chemical Type: Mixture

Melting Point: N/A °F

Boiling Point: N/A °F

Specific Gravity: 1.13

Molecular Weight: N/A

Packing Density: 9.46

Vapor Pressure: N/AV

Vapor Density: N/AV

Solubility: N/AV

Evaporation Rate: SLOWER THAN ETHER

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Incompatible Materials

Strong acids or alkaline materials.

Hazardous Decomposition Products

NITROGEN OXIDES, CO, CO2

11. Toxicological Information

Conditions Aggravated By Exposure

Asthma, Allergies

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

No Data Available...

MATERIAL SAFETY DATA SHEET

Sikadur® 42 Grout-Pak Part A

14. Transport Information - Continued

Proper Shipping Name

NOT REGULATED PER D.O.T.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

16. Other Information

HMIS Rating

Health: 2

Fire: 1

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supersedes A Previous MSDS Dated: 03/29/2001

Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000