

MATERIAL SAFETY DATA SHEET



PROSOCO, Inc.

I PRODUCT IDENTIFICATION

MANUFACTURED FOR: PROSOCO, Inc.
3741 Greenway Circle
Lawrence, KS 66046

EMERGENCY TELEPHONE NUMBERS:
8:00 AM – 5:00 PM CST Monday-Friday: 785-865-4200
NON-BUSINESS HOURS (INFOTRAC): 800-535-5053

PRODUCT TRADE NAME: Sure Klean® Strippable Masking

MANUFACTURER'S NAME AND ADDRESS: PROSOCO, Inc.
3741 Greenway Circle
Lawrence, KS 66046

II HAZARDOUS INGREDIENTS

CHEMICAL NAME	(COMMON NAME)	CAS NO.	NFPA CODE	ACGIH TLV/TWA	OHSA PEL/TWA
Titanium dioxide	Titanium dioxide	13463-67-7	1,0,0,-	10 mg/m3	15 mg/m3 (for total dust)

III TYPICAL PHYSICAL DATA

	BOILING POINT (°F)	VAPOR PRESSURE (mm Hg)	VAPOR DENSITY (Air = 1)	EVAPORATION RATE (Butyl Acetate = 1)
Titanium dioxide	NA	NA	NA	NA
	pH	SPECIFIC GRAVITY	SOLUBILITY IN WATER	APPEARANCE AND ODOR
Sure Klean® Strippable Masking	9.9	1.04 (@ 20°C)	100%	Viscous, white liquid. No solvent odor

IV FIRE AND EXPLOSION HAZARD DATA

EMERGENCY OVERVIEW

Sure Klean® Strippable Masking is a free-flowing liquid with a creamy consistency. It may cause irritation to the eyes, skin, and respiratory tract. If ingested, it may cause mild irritation and abdominal discomfort.

FLASH POINT (METHOD): >229°C (444°F)

AUTOIGNITION TEMPERATURE: 449°C (840°F)

FLAMMABLE LIMITS: Not flammable. Dried coating is an ordinary combustible.

EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Liquid material will not burn, no special instructions available. Use methods appropriate for surrounding materials. For dried paint or dried organic coating fires, use methods appropriate for wood, paper and similar combustibles.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide

V HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Inhalation, Ingestion, Skin contact, Eye contact.

CARCINOGEN INFORMATION: Not listed (IARC, NTP, OSHA).

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Lung disease.

EFFECTS OF OVEREXPOSURE: Tissue irritation.

EYE CONTACT: Can cause minor irritation, tearing and reddening.

SKIN CONTACT: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.

INGESTION: Mildly irritating to mouth, throat and stomach. Can cause abdominal discomfort.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Immediately flush exposed area with water for at least 20 minutes, holding eyelids apart to ensure flushing of the entire eye surface. Seek medical attention.

SKIN CONTACT: Immediately flush exposed area with soap and water for at least 10 minutes. If irritation persists, or if contact has been prolonged, get medical attention. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth by a trained person. If breathing is difficult, give oxygen. Get medical attention.

INGESTION: Seek immediate medical assistance. Do not induce vomiting unless instructed by physician. Never give anything by mouth if person is unconscious.

VI REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: Temperatures above the high flashpoint of this combustible material in combination with sparks, open flames, or other sources of ignition. Contamination. Do not Freeze.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Oxides of carbon.

VII SPILL OR LEAK PROCEDURES

SPILL, LEAK, WASTE DISPOSAL PROCEDURES: Restrict traffic and ventilate area. Collect for disposal. Clean up remaining materials from spill with suitable absorbent. Dispose of unused product, container and spill residues in accordance with state, local and federal regulations.

WASTE DISPOSAL METHODS: Dispose of in a manner approved for this material or in an approved waste handling facility. Consult federal, state and local regulations for proper disposal methods. Product as supplied is not classified as a hazardous waste under USEPA regulations. Dried coating may be disposed of as ordinary trash.

VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Not normally required if good ventilation is maintained.

VENTILATION: General ventilation usually adequate.

PROTECTIVE CLOTHING: Wear protective clothing as needed to avoid prolonged skin contact. Clothing selection is dependent on application methods.

PROTECTIVE GLOVES: Wear cloth, leather or appropriate impermeable gloves to avoid skin contact.

EYE PROTECTION: Wear safety glasses with side shields to avoid eye contact. Additional splash protection may be required depending on application methods.

OTHER PROTECTIVE EQUIPMENT: Provide eyewash or portable eyewash. Provide source of clean water for skin. Personal protective clothing and use of equipment must be in accordance with 29 CFR 1910.133 and 29 CFR 1910.132.

IX SPECIAL PRECAUTIONS

WORK PRACTICES: Proper work practices and planning should be utilized to avoid contact with workers, passersby, and non-targeted surfaces. See the Product Data sheet and label for specific precautions to be taken during use. Wash hands after handling product.

X REGULATORY INFORMATION

SHIPPING: Classified as non-hazardous for shipping for USDOT and IATA. NMFC Classification: 149980 sub 2. Class rate: 55

SARA 313 REPORTABLE:

CHEMICAL NAME

CAS

UPPERBOUND CONCENTRATION % BY WEIGHT

None

CALIFORNIA PROPOSITION 65:

This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

XI OTHER

MSDS Status:

Date of Revision: March 22, 2005

For Product Manufactured After: March 22, 2005

Changes: New formulation.

Item #: 20046

Approved By: Regulatory Department

DISCLAIMER:

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. **PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described.** This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

DATE OF PREPARATION: March 22, 2005