

PRODUCT SUBMITTAL



WIRE-BOND[®]

Aqua Flash 500 Primer



Description:

A one component solvent-base, high tack primer specifically designed to promote maximum adhesion of the Aquaflash 500 membrane waterproofing on all vertical and horizontal surfaces when the substrate is either not dirt free or when membrane will not adhere properly.

Application:

Apply by spray, brush or long nap roller to all surfaces in an even coat at 250-300 square feet per gallon. At 75°F, allow primer to dry one hour minimum, 8 hours maximum. Primer has satisfactory cure when surface is tacky, but does not transfer when touched. If the Aquaflash 500 membrane is not applied within the maximum dry time, re-prime. Do not apply below 25°F.

Packaging:

Aquaflash 500 solvent-base, high tack primer is packaged in 5 gallon pails.



Caution:

Use with adequate ventilation and avoid breathing of vapors. In closed areas, workmen should wear approved breathing apparatus, protective clothing and eye protection. Avoid ingestion. See MSDS sheets for further information.

Corporate Office: 400 Roundtree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761



Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 240988 Charlotte, NC 28224

www.wirebond.com

Mailing Address: P.O. Box 13124 Memphis, TN 38113