

PRODUCT SUBMITTAL

Blok-Flash[®]

DESCRIPTION

BLOK-FLASH[®] delivers the surest, most cost-effective control of moisture and mold-growth in exterior single wythe C.M.U. wall systems. Blok-Flash[®] is a tough, lightweight embeddable flashing system suitable for use at all flashing/weep locations, including base of wall, above door and window openings, above bond beams, in parapet walls, basements, and wherever flashing is necessary. It provides 10 times greater bond at the exterior bed-joint than a through-wall membrane system, with no water penetration, no by-pass, and rapid expulsion of moisture.

SHORT FORM SPEC

System of CMU cell flashing pans and interlocking CMU web covers made from high-density polyethylene incorporating chemical stabilizers that prevent UV degradation.

Cell flashing pans have integral weep spouts that are designed to be built into mortar bed joints and weep collected moisture to the exterior of CMU walls and that extend into the cell to prevent clogging of mortar.

Product: Subject to compliance with requirements, provide "Blok-Flash[®]" by Mortar Net USA, Ltd.

MANUFACTURER

Mortar Net USA, Ltd.

541 South Lake Street, Gary, IN 46403

Telephone: (800) 664-6638

Fax: (219) 939-3877

Email: info@mortarnet.com

Website: www.MortarNet.com

Specifier Note: Blok-Flash[®] is a high-density polyethylene composition molded into a .0625 inch thick (1.59 mm) flashing pan with .3125 inch (7.94 mm) perimeter flanges. The .0625 inch (1.59 mm) concaved weep spout with a .20 inch (5.08 mm) x .64 inch (16.26 mm) opening and a 45 degree drip edge extends 1.0 inch (25.4 mm) from the outer flange. The inner and outer flanges are spaced to allow for 1.0 inch of mortar bond between the upper and lower course of C.M.U. in 8", 10", or 12" wall systems. The weep spout ceiling extends 3.5 inches (88.9 mm) from the outer flange into the center of the pan and acts to suspend mortar, keeping the weep channel clear. Blok-Flash[®] is impervious to water and includes chemical stabilizers to protect against UV degradation.



R062606

	C.M.U. Type	Height	Width	Length
BF08 - Blok-Flash 8"	8" (7-5/8")	0.3125" (7.94mm)	5.625" (5142.88mm)	6.75" (171.45mm)
BF10 - Blok-Flash 10"	10" (9-5/8")	0.3125" (7.94mm)	7.625" (193.68mm)	6.75" (171.45mm)
BF12 - Blok-Flash 12"	12" (11-5/8")	0.3125" (7.94mm)	9.625" (244.48mm)	6.75" (171.45mm)
Units Per Carton: 100 pans with approximately 90 connector bridges				

DATE: _____

PROJECT: _____

FIRM: _____ PHONE: _____

APPROVAL: _____ DATE: _____

GENERAL CONTRACTOR: _____

BID DATE: _____

COMMENTS: _____

