

## Technical Data

## CITRUS PEEL™ (J-48)

Citrus Based Floor Stripper & Degreaser **V.O.C. COMPLIANT**

### PRODUCT DESCRIPTION:

Citrus Peel is a heavy duty concrete stripper and degreaser that was developed from citrus oranges. It is V.O.C. compliant, with a pleasant orange smell and is easy to work with. It is used full strength for stripping and degreasing and for general cleaning purposes.

### PURPOSE:

Citrus Peel is designed for stripping, degreasing and cleaning all types of concrete. It is ideal for concrete floor applications when it is necessary to remove dirt, tire marks, oil spills, grease and other contaminants.

Citrus Peel will also strip certain curing compounds. It is an ideal application for warehouses, industrial plants, food processing plants, automotive plants, parking garages, plazas and service stations.

### ADVANTAGES:

- Stripper and degreaser
- Multi-purpose cleaner
- V.O.C. Compliant
- Pleasant orange smell

### SPECIFICATIONS:

Viscosity – 1.0 CPS  
Emulsifiable – Yes  
V.O.C. Compliant – Yes  
Color – Amber  
Odor – Orange Smell  
Weight – 7.14 lbs./gal.  
Shelf Life – 1 Year

### APPLICATION INSTRUCTIONS:

Apply Citrus Peel full strength for removing heavy dirt buildup, tire marks, oil spills, grease, hydraulic fluid and any difficult to remove contaminants from the concrete surface. Apply Citrus Peel full strength to the entire floor.

Allow Citrus Peel to soak into the surface for 20 minutes (longer soak times may be necessary for removal of curing compounds). Work it in with a stiff broom or floor buffer (swing scrubber). After scrubbing the floor, rinse thoroughly with water, then vacuum or squeegee dry the entire floor.

Re-application may be necessary for extremely dirty, stained floors, or hard-to-remove curing compounds.

### APPROXIMATE COVERAGE:

Stripping/Degreasing/Heavy Duty Cleaning: 100-200 sq. ft./gal. (2.5-4.9 m<sup>2</sup>/L).  
Normal Cleaning: 400-500 sq. ft./gal. (9.8-12.3 m<sup>2</sup>/L).

### PACKAGING:

55 gal. drums (208L), 5 gal. pails (18.9L), 1 gal. units (3.8L).

### CLEANUP:

Tools and equipment – use water.

### LIMITATIONS:

Shelf life is one year. Use Citrus Peel only on concrete or masonry surfaces. **Do Not Use On Painted Walls.**

Citrus Peel will adversely affect vegetation.

Citrus Peel and the materials it removes might be hazardous and should be disposed of according to all local, state and federal regulations. Do not allow to flow into waterways.

### WARNING:

- Use with adequate ventilation
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting

If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Keep away from heat, spark, open flame and other possible sources of ignition. Reseal container after each use. Wear protective clothing, gloves, and goggles. Read MSDS before using product.

### TECHNICAL SERVICES:

Contact the technical staff for assistance at:

1-866-329-8724 • 1-913-233-1750 • FAX: 1-913-279-4806

[daytonsuperiorchemical.com](http://daytonsuperiorchemical.com)

### WARRANTY

Warranty, Warranty Disclaimer and Exclusive Remedy – Dayton Superior Corporation warrants, for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by ("the Company"), the product is free of manufacturing defects and conforms to ("the Company's") published specifications in force on the date of acceptance by ("the Company") of the order. ("the Company") shall only be liable under this warranty if the material has been applied, used, and stored in accordance with ("the Company") instructions in the product's technical data sheet.

The purchaser must examine the product when received and promptly notify ("the Company") in writing of any non-conformity before the product is used, or no later than 30 days after such non-conformity is first discovered. If ("the Company"), in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty.

Only a ("Company") officer is authorized to modify this warranty. The sales information on the ("the Company's") website and received by the customer during the sales process does not supersede this warranty and the specifications of the product in force on the date of sale. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

Limitation of Liability – Dayton Superior Corporation shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustrations of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, this Agreement, even if ("the Company") could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this agreement, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.

Dayton Superior Specialty Chemical Corp • 4226 Kansas Avenue, Kansas City, KS 66016  
Telephone (913) 233-1750 • Fax (913) 279-4806 • [daytonsuperiorchemical.com](http://daytonsuperiorchemical.com)