

E-CON™

Evaporation Reducer For Plastic Concrete

MANUFACTURER

L&M Construction Chemicals, Inc.
14851 Calhoun Road
Omaha, NE 68152
Phone: (402)453-6600
FAX: (402)453-0244
Website: www.lmcc.com

PRODUCT DESCRIPTION

E-CON is a concentrated, odorless, water-based polymer liquid that, when placed on fresh concrete, forms a thin, continuous monomolecular film that temporarily reduces rapid moisture loss from the concrete surface. E-CON reduces contractor field problems with exposed exterior concrete by minimizing surface crusting and plastic shrinkage cracks.

E-CON helps achieve superior quality flatwork. It minimizes water evaporation and controls the surface condition of the slab to aid in meeting finishing schedules. It is effective in minimizing rapid drying conditions due to high temperatures, low humidity, high winds and direct sunlight.

Basic Use: E-CON forms a monomolecular film on plastic concrete surfaces that prevents rapid moisture loss. The protective shield formed usually lasts as long as the concrete remains plastic, despite successive floating and troweling operations. No residue remains after the concrete hardens.

Use E-CON evaporation control to aid with plain concrete, silica fume concrete, concrete resurfacers, and all cementitious floor hardeners after screeding.

FEATURES & BENEFITS

- Reduces plastic shrinkage cracks.
- Reduces evaporation rates up to 80% in wind and 40% in hot sunlight.
- Minimizes surface crusting
- Cement hydration is improved.
- Improves durability by controlling evaporation.
- Remains effective after screeding and first floating operation.
- Non-residual.
- Economically concentrated

ESTIMATING

E-CON is available in 1 quart (.95 liter), 1 gallon (3.8-liter), 5-gallon (18.9-liter) and 55-gallon (208-liter) containers. Each container is clearly identified with product name and batch number.

Dilution Rate - 10 parts water: 1 part E-CON

Coverage - 200-400 ft²/gallon (5-10 m²/liter) after dilution.

TECHNICAL DATA

Color - pink (disappears completely upon exposure to sunlight or other ultraviolet light source).

VOC compliant.

INSTALLATION

Mixing: Shake or mix concentrate before dilution. Add 10 parts water to 1 part **E-CON Concentrate**. Mix or shake again until thoroughly blended.

Application: Use clean, dry spray equipment with fogging tip. Spray immediately after bull floating. In extreme drying conditions, re-apply additional material as needed. Use on fresh concrete as well as between each shake application. Apply lightly on hard-to-trowel floor areas.

Concrete plastic shrinkage cracks and resulting stress cracks are a strong possibility when the rate of evaporation exceeds 0.2 pounds/ft²/hour (1.0 kg/m²/hour). Evaporation rate is a direct function of relative humidity, concrete temperature, air temperature, and wind velocity. The use of E-CON is recommended when the rate of evaporation of the concrete approaches or exceeds this level.

ACI Committee 305, "Recommended Practice for Hot Weather Concreting," developed a chart, which graphically determines evaporation rates under a given set of job site conditions. Copies are available from L&M upon request.

FOR BEST RESULTS:

- Do not use concentrated.
- Use at proper dilution rate.
- Do not use as curing compound.
- Apply only as fine spray.



E-CON



- Avoid puddling.
- Immediately wipe up any wet residue from hardened concrete surfaces and rinse surface to avoid stains.
- Do not allow to freeze.

PRECAUTIONS

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not take internally. Wear skin and eye protection.

Please refer to Product Material Safety Data Sheet (MSDS) before using.

STORAGE/SHELF LIFE

E-CON containers are to be kept tightly sealed and stored in a cool, dry place. Shelf life is one year when stored properly, between 40°-105°F (5°-40° C). Keep from freezing.

FAX ON DEMAND/WEBSITE

L&M's exclusive Fax On Demand and its convenient internet website offer instant access to Tech Data Sheets, Material Safety Data Sheets, product updates, and other useful information. Simply dial 800-839-9887 or visit www.lmcc.com and follow the easy steps.

LIMITED WARRANTY

This product is warranted to be free of defects in material and workmanship, and conform to L&M Construction Chemicals ("L&M") quality control standards. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind, expressed or implied including but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose. Satisfactory results depend upon many factors beyond L&M's control. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from his or her direct use, indirect use or consequential to their use of the product. L&M shall not be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use or inability to use the product. L&M's sole responsibility shall be to replace that portion of the product which proves to be defective. Any warranty claim must be made within six (6) months from the date of the claimed breach. This limited warranty applies only if the product was properly installed and used according to all instructions and was properly stored prior to use.

For Professional Use Only.

©2005, L&M Construction Chemicals, Inc.