



THE EUCLID CHEMICAL COMPANY

19218 REDWOOD ROAD • Cleveland, OH 44110
(216) 531-9222 • (800) 321-7628 • FAX (216) 531-9596
www.euclidchemical.com

EUCO SOLVENT

CLEAN-UP AND FLOOR STRIPPER PRODUCT

EUCO SOLVENT is a high-strength solvent for numerous uses from tool clean-up to membrane removal. It is a pure liquid and contains no added fillers or solids.

PRIMARY APPLICATIONS

- Tools and equipment
- Removal of resin based curing membranes and sealers from floor surfaces.
- Breakdown of oil, grease and tar build-up.
- Clean-up of epoxy equipment and tools
- Troweling aid for epoxy mortars.

FEATURES / BENEFITS

- High strength for fast clean-up
- Multiple components for maximum effectiveness

PACKAGING

EUCO SOLVENT is packaged in 5 gal (18.9 liter) pails and 4/1 gal (3.8 liter) units per case.

COVERAGE

Tool Clean-Up: Clean tools with brushes before resin residue has hardened. If the resin has hardened, submerge the tools in EUCO SOLVENT until the residue has softened and can be scraped away.

Floor Stripping: For solvent based curing compound removal, an application rate of 100 ft²/gal (2.45 m²/liter) will remove most of the sealer. (This product may not be effective in removing some water based curing and sealing products.) Cured epoxy sealers and coatings may require 2-3 applications for complete removal.

Shelf Life: 2 years in original, unopened package.

Appearance

EUCO SOLVENT is a clear, low viscosity liquid.

DIRECTIONS FOR USE

Surface Preparation- Resin removal is easiest if the material has not hardened. Floor applications will be quickened if the coating surface has been scored and scratched.

Mixing- EUCO SOLVENT requires no premixing. The product is ready for use directly from the container.

Placement- Apply EUCO SOLVENT directly on the unwanted resin. Allow to soften for 5-10 minutes. Reapply additional solvent and begin resin removal.

PRECAUTIONS / LIMITATIONS

- Do not use near open flames.
- Use only in well ventilated areas.
- If HVAC intake ducts will distribute solvent odor into adjoining occupied areas of the building, care should be taken to block these ventilation vents.
- Always wear protective clothing (rubber gloves, eye protections, etc...).



Euco Solvent-2.04

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for six (6) months from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.