

**DESCRIPTION AND USE**

Defacer Eraser® Graffiti Wipe is an easy-to-use graffiti remover that does not contain methanol, methylene chloride or other halogenated solvents prohibited on many projects. Graffiti Wipe removes a variety of graffiti stains from most smooth masonry, split-faced concrete block, wood and metal surfaces.

**ADVANTAGES**

- Removes spray-painted graffiti from a huge variety of masonry and nonmasonry surfaces.
- Wipes graffiti off many surfaces with just a towel.
- Rinses easily with cold or hot water.
- Excellent chemical assist for cold-water removal of Defacer Eraser® Sacrificial Coating SC-1.
- Contains active citrus fruit extracts.

**Limitations**

- Product efficiency is reduced during cold weather.
- May damage synthetic or reflective glass.

**TYPICAL TECHNICAL DATA**

FORM: Clear liquid with a citrus odor  
 SPECIFIC GRAVITY: 0.910  
 TOTAL SOLIDS: NA  
 pH: NA  
 WT./GAL.: 7.57 lbs.  
 FLASH POINT: 130°F (54°C) ASTM D 3278  
 FREEZE POINT: <-22°F (<-30°C)

**PREPARATION**

**Protect** people, vehicles, property, painted surfaces, plants and all surfaces not set for cleaning from product, residue, splash, rinse, fumes and wind drift. Protect and/or divert pedestrian and auto traffic. Some metal finishes and glass installed in recent years may be damaged by product. Test or protect if necessary. Sure Klean® Strippable Masking is not appropriate for use with this product.

**Surface and Air Temperatures**

Cleaning effectiveness is reduced when surface and air temperatures fall below 50°F (10°C). Do not apply at temperatures below 40°F (4°C). If freezing conditions exist prior to application, let masonry thaw.

**APPLICATION**

**Before use, read “Preparation” and “Safety Information.”**

**ALWAYS TEST** each type of surface, paint coating and graffiti stain for suitability and results before overall application. Test using the following application instructions. Let tests dry thoroughly before inspection.

**Dilution**

Use in concentrate. DO NOT DILUTE OR ALTER.

**Smooth or Protected Surface Application**

1. Apply Graffiti Wipe liberally to a towel or piece of cloth. Scrub the surface with saturated cloth until the graffiti is removed.
2. Wipe the surface with a dry cloth to remove excess Graffiti Wipe and graffiti residue. If necessary, rinse the surface with hot or cold water to remove any remaining product residue.

**Rough/Porous\* or Unprotected Surface Application**

1. Apply Graffiti Wipe with a brush or low-pressure spray.
2. Allow to dwell for 3-5 minutes.
3. Pressure-water rinse. Hot water is preferable.

\*Also for protected rough or porous surfaces.

Note: Removal results may be unsatisfactory if Graffiti Wipe dries on the surface. If testing indicates long dwell periods are required, reapply to prevent drying. Heavy graffiti staining may

<b>Graffiti Wipe is recommended for these substrates. Always test. Coverage is in sq.ft./m. per gallon.</b>			
<i>Substrate</i>	<i>Type</i>	<i>Use?</i>	<i>Coverage</i>
<b>Architectural Concrete Block</b>	Burnished	yes	75-150 sq.ft. 7-14 sq.m.
	Smooth	yes	
	Split-faced	yes	
	Ribbed	yes	
<b>Concrete</b>	Brick	yes	75-200 sq.ft. 7-19 sq.m.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
	Cast-in-place	yes	
<b>Fired Clay</b>	Brick	yes	150-250 sq.ft. 14-23 sq.m.
	Tile	yes	
	Terra Cotta	yes	
	Pavers	yes	
<b>Marble, Travertine, Limestone</b>	Polished	yes	200-400 sq.ft. 19-37 sq.m.
	Unpolished	yes	100-200 sq.ft. 9-19 sq.m.
<b>Granite</b>	Polished	yes	250-500 sq.ft. 23-46 sq.m.
	Unpolished	yes	200-400 sq.ft. 19-37 sq.m.
<b>Sandstone</b>	Unpolished	yes	75-150 sq.ft. 7-14 sq.m.
<b>Slate</b>	Unpolished	yes	200-400 sq.ft. 19-37 sq.m.

Also effective on wood and metal surfaces.  
 Always test to ensure desired results. Coverage estimates depend on surface texture and porosity.

Graffiti Wipe

require more than one application. Other PROSOCO products for effective stripping of multiple graffiti layers include Sure Klean® Fast Acting Stripper and Enviro Klean® Safety Peel 1. Call Customer Care at 800-255-4255 or visit [www.prosoco.com](http://www.prosoco.com) for more information on these and other paint, coating and graffiti-removal products.

**Repainting:** Wood surfaces should be sanded lightly or prepared as required before repainting.

### Removing Defacer Eraser® Sacrificial Coating SC-1

1. Apply Graffiti Wipe with a brush or low-pressure spray.
2. Allow to dwell for 3-5 minutes.
3. Pressure water rinse. Hot water is preferable.
4. Reapply Defacer Eraser® Sacrificial Coating SC-1 to restore graffiti protection. See SC-1 product data sheet for more information.

### Clean Up

Water cleaning should be sufficient for cleanup. Dried residue may be cleaned with high-flash aromatic naphtha or mineral spirits.

## SAFETY INFORMATION

**Warning:** Combustible liquid and vapor. Harmful if swallowed. Causes skin, eye and respiratory irritation. For use by professional applicators only. Keep out of the reach of children.

### Precautionary Measures

**Contains:** Terpene hydrocarbons, n-methylpyrrolidone and alkyl phenol ethoxylates. Vapors may ignite from local or remote ignition source. Keep away from heat, sparks and flame. Do not apply to heated surfaces as flash point may be exceeded. Do not cut, grind, weld, or drill on or near this container, even if empty.

**Use only with adequate ventilation.** Do not breathe vapors or mist. Ensure fresh air entry during application and until vapors are gone. Avoid exposing building occupants to fumes and mists. If you experience respiratory irritation, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted, NIOSH-approved respirator. Avoid contact with eyes, skin and clothing. Wear splash goggles to prevent splash to eyes and protective clothing as needed to avoid exposure to skin. Wash thoroughly after handling.

### First Aid

**Ingestion:** If conscious, give water and get immediate medical attention. If vomiting occurs, keep head below hips to avoid aspiration.

**Eye Contact:** Rinse thoroughly for 15 minutes. Get medical attention if irritation persists.

**Skin Contact:** Rinse thoroughly with soapy water. Get medical assistance if irritation persists. Launder contaminated clothing before reuse.

**Inhalation:** Remove to fresh air. Give artificial respiration if not breathing. Get medical attention.

### 24-hour emergency information: INFOTRAC at 800-535-5053

**Storage and Handling:** Store away from heat and open flames in cool, shady, dry place with adequate ventilation. Keep tightly closed when not dispensing. Do not reuse container or remove the label. **If spilled,** follow all precautionary instructions. Keep from water and soil. Contain and absorb with inert material. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Do not alter** or dilute the product except as specified. Do not use for any other purpose. Always protect passersby, building occupants and nonmasonry surfaces. Read the MSDS and label for additional precautionary information.

**Container Disposal:** Hazardous when empty. Follow all precautionary instructions. Drain thoroughly and dispose of in a sanitary landfill (check local restrictions).

**Shelf Life:** 2 years from date of manufacture in properly stored, unopened container.

## WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects.

**Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

## CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at [www.prosoco.com](http://www.prosoco.com) for the name of the Defacer Eraser® representative in your area.