



## Accent-Liquid Release™ Characteristics and Applications

### Description

Accent-Liquid Release™ is a colorless bondbreaker, formulated to prevent Tooling™ from sticking to the still plastic concrete or stampable overlays. Accent-Liquid Release™ is used exclusively with the Artisan Overlay™ System where powder release agents cannot be used.

Accent-Liquid Release™ is used when a mottled, antiqued appearance is NOT desired and is available in a 5-gallon unit or 55-gallon drum.

- Interior or Exterior
- Alternative to Powder Releases
- Reduces clean up efforts

### Basic Uses

Accent-Liquid Release™ is used as an alternative to pigmented powdered release bondbreakers with Impressions™ and Artisan Overlay™ systems.

### Use With These Products or Systems

- Impressions™
- Tooling™
- FauxCrete™
- Artisan Overlay™
- Signature Seal VOC™
- Signature Satin 400™
- Premium Seal VOC 100™
- AquaClear VOC™
- Magnum Seal™

### Application

Using a pump-up type industrial sprayer, apply a liberal misting of Accent-Liquid Release™ to both the concrete and the Tooling™ or Artisan Overlay™ immediately prior to the stamping process. Only apply the Accent-Liquid Release™ to small areas, approximately 10 to 15 square feet (1–1.4 square meters) to avoid evaporation of Accent-Liquid Release™.

### Coverages

Approximately 150 square feet per gallon (3.7 square meter per liter).

### Packaging

5-gallon (18.9 L) pails, 24 pails per pallet.  
55-gallon (207.9 L) drums, 4 drums per pallet.

### Storage and Shelf Life

Store in a cool, dry area.

Shelf life is 1 year from date of manufacture in original unopened containers.

### Clean Up

Wash off the Accent-Liquid Release™ from the Tooling™ with clean water.

### Limitations

Do not use Accent-Liquid Release™ below 40°F (4.4°C). Do not trowel Accent-Liquid Release™ into the still plastic concrete.

### Precautions

Review Material Safety Data sheet prior to product use and for additional information.

1. KEEP OUT OF REACH OF CHILDREN.
2. Avoid ingestion.
3. Avoid excessive inhalation of vapors or mist.
4. Avoid contact with skin and eyes.
5. Use appropriate protective clothing, including gloves, goggles and fitted approved OSHA-NIOSH respirators.

### Warranty

Legacy™ Decorative Concrete Systems, Inc. warrants that these products will be free from defects, and will perform as specified in the Technical Data Sheet, provided that storage, use and application of product are in accordance with manufacturer's recommendations and application instructions. The exclusive remedy of the user or buyer and the limit of the liability of this company for product proven defective shall be the purchase price paid by the user or buyer for the quantity of the Legacy™ Decorative Concrete Systems, Inc. products involved. Legacy™ Decorative Concrete Systems, Inc. shall not be liable for indirect, incidental, consequential, or special damages, whether due to breach of warranty or tort (including without limitation Legacy™ Decorative Concrete Systems, Inc.).

### Manufacturer

Legacy™ Decorative Concrete Systems, Inc.

4021 Color Plant Rd.  
Springfield, IL 62702

P.O. Box 8406  
Springfield, IL 62791-8406

Tel. 217-522-6737  
Toll Free 866-684-9394  
Fax. 866-684-9395

### Legacy Distribution Centers

4021 Color Plant Rd.  
Springfield, IL 62702

1251 West Durst Rd.  
Rialto, CA 92376

670 Allen Rd.  
Carlisle, PA 17013