



Accent-Colour Release™ Characteristics and Applications

Description

Accent-Colour Release™ is a pigmented dry powder release for the stamping tools designed to be used when a mottled, antiqued appearance is desired. Accent-Colour Release™ is a pigmented bondbreaker, formulated with proprietary components and high purity pigments that are UV resistant and streak free. Accent-Colour Release™ is available in 20 Classic Series colors and 8 Signature Series colors designed to add contrast or antiquing effects with Colour-Hard™ or ColorFlo® Liquid Color integral colors. Accent-Colour Release™ is packaged in 30 lb. plastic pails. Refer to Legacy Colors LEG-CSC1 Color Card.

- UV Resistant
- Streak Free
- Custom Color Matching Available

Basic Uses

Accent-Colour Release™ is used in creating antiquing effects for Impressions™ and FauxCrete™.

Use With These Products & Systems

- ColorFlo® Liquid Color
- Colour-Hard™
- Impressions™
- FauxCrete™
- Signature Seal VOC™
- Signature Satin 400™
- Premium Seal VOC 100™
- Magnum Seal™
- AquaClear VOC™

Composition

Accent-Colour Release™ is formulated as a fine powder, utilizing UV resistant and streak free pigments.

Colors

Accent-Colour Release™ is available in 20 Classic Series and 8 Signature Series colors. Refer to Legacy Color Card LEG-CSC1 for available colors.

Application

Preparatory work: Protect adjacent areas from contamination during application. Estimate amount of Accent-Colour Release™ required for project. Stage Accent-Colour Release™ outside the formwork, along and adjacent to work site. Avoid application in windy conditions.

Accent-Colour Release™ can pack tightly in container during shipment and storage. Loosen and fluff the Accent-Colour Release™ prior to broadcasting to ensure a more even application. Only broadcast the Accent-Colour Release™ to small areas, approximately 10 to 15 square feet

(1 to 1.4 square meters) immediately prior to the stamping process. Broadcast the Accent-Colour Release™ in a thin, uniform layer covering the colored, troweled concrete surface. Do not over apply Accent-Colour Release™. Over application can decrease texture and detail. Do not trowel Accent-Colour Release™ into the concrete surface. Stamping process should begin as soon as the Accent-Colour Release™ has been applied.

Remove residual Accent-Colour Release™ when concrete surface is sufficiently cured. Excess Accent-Colour Release™ should be first swept from concrete surface, and then pressure washed to achieve desired antiqued effect. Allow concrete surface to dry thoroughly, then seal.

Colors and Coverages

Accent-Colour Release™ is available in 20 Classic Series and 8 Signature Series colors. One pail of Accent-Colour Release™ covers approximately 1000-1200 square feet (93-112 m²).

Packaging

Accent-Colour Release™: 30-pound (13.6 kilogram) pail, 36 pails per pallet.

Storage and Shelf Life

Store in a cool, dry area.

Shelf life is 1 year from date of manufacture in original unopened containers.

Clean Up

Wash Accent-Colour Release™ from Legacy Tooling™ with clean water.

Limitations

Do not trowel Accent-Colour Release™ into the concrete surface.

Accent-Colour Release™ should not be used as a primary coloring agent.

Avoid application in windy conditions.

Precautions

Review Material Safety Data Sheet prior to product use and for additional information.

1. KEEP OUT OF REACH OF CHILDREN.
2. Avoid ingestion.
3. Avoid contact with skin and eyes.
4. Use appropriate protective clothing, including gloves, goggles and fitted approved OSHA-NIOSH respirators.

Warranty

Legacy™ Decorative Concrete Systems, Inc. warrants that these products will be free from defects, and will perform as specified in the Technical Data Sheet, provided that storage, use and application of product are in accordance with manufacturer's recommendations and application instructions. The exclusive remedy of the user or buyer and the limit of the liability of this company for product proven defective shall be the purchase price paid by the user or buyer for the quantity of the Legacy™ Decorative Concrete Systems, Inc. products involved. Legacy™ Decorative Concrete Systems, Inc. shall not be liable for indirect, incidental, consequential, or special damages, whether due to breach of warranty or tort (including without limitation Legacy™ Decorative Concrete Systems, Inc.).

Manufacturer

Legacy™ Decorative Concrete Systems, Inc.

4021 Color Plant Rd.
Springfield, IL 62702

P.O. Box 8406
Springfield, IL 62791-8406

Tel. 217-522-6737
Toll Free 866-684-9394
Fax. 866-684-9395

Legacy Distribution Centers

4021 Color Plant Rd.
Springfield, IL 62702

1251 West Durst Rd.
Rialto, CA 92376

670 Allen Rd.
Carlisle, PA 17013