

Oil & Grease Stain Remover

poultice cleaner for embedded oil & grease stains

DESCRIPTION AND USE

Stand Off® Oil and Grease Stain Remover is a poultice cleaner for pulling stubborn oil and grease stains out of pavers, concrete, stone and other porous surfaces. Just pour Oil & Grease Stain Remover on the embedded stain. It spreads out to make an instant poultice – no mixing, troweling, plastic covering or tape needed.

As the poultice dries, it pulls the contaminants out of the substrate, capturing them in its highly absorbent blend of batter-thick surfactants, solvents and powders. After a 5-8 hour dwell, simply sweep up the dried poultice and its absorbed contaminants for easy disposal.

ADVANTAGES

- Works on old, deeply-set stains.
- Easy to use. No mixing or scrubbing needed.
- Works on concrete, pavers, block, stone, tile and brick.
- Leaves no residue.
- Removes motor oil, brake and power-steering fluids, anti-freeze, hydraulic fluids, cooking oils, food grease and other oil-based stains.
- Won't discolor stone.
- Safe on marble, granite, limestone and travertine.

Limitations

- Not recommended for asphalt surfaces.

TYPICAL TECHNICAL DATA

FORM: Viscous, white liquid, slight citrus fragrance
SPECIFIC GRAVITY: 0.80
TOTAL SOLIDS: NA
pH: 10.5
WT/GAL: 6.66 lbs.
FLASH POINT: > 200°F (> 93°C) ASTM D 3278
FREEZE POINT: 32°F (0°C)
SHELF LIFE: 2 years in unopened container

VOC Information

Maximum VOC Content: 4%

PREPARATION

Protect people, vehicles, plants, nearby property and non-masonry surfaces from contact with product. Test all surfaces that may come in contact for compatibility. Immediately rinse non-target materials with water.

Surface and Air Temperatures

Best air and surface temperatures for cleaning are 50°F (10°C) or above. If freezing conditions exist before application, let substrate thaw.

Equipment

Use broom or other stiff-bristled brush, and dustpan to sweep up dried poultice. Though not required, high-pressure air can be used to “blow-out” extremely porous surfaces after sweeping.

APPLICATION

Before use, read “Preparation” and “Safety Information.”

ALWAYS TEST each type of surface and each type of stain for suitability, dwell-time and results. Use the following application instructions.

Dilution

Use in concentrate. Do not dilute. Shake well before use.

Coverage Rates

One quart will clean approximately 6 sq.ft. (0.5 sq.m.)

One gallon will clean approximately 24 sq.ft. (2 sq.m.)

Application Instructions

1. Scrape debris and buildup from surface. Do not pre-wet.
2. Shake well. Pour onto the oil-stained surface until it completely covers the stain. The batter-thick poultice will automatically reach its required thickness as it spreads out across the stain.
3. Let the poultice dry for 5-8 hours or overnight. Protect from pedestrian traffic and rain during dwell period. Regarding rain protection, a plastic “tent” over the poultice will allow proper drying. Avoid using tightly-adhered plastic covers. Dry times may vary with environmental conditions such as temperature, wind and humidity. The poultice surface develops cracks as it contracts and dries. A fully developed network of cracks indicates the poultice is completely dry.
4. Sweep up the dry powder and dispose. On porous substrates, pressure water rinsing may facilitate removal of poultice residue.

Most oil and grease stains can be cleaned with one application. Severe, deeply-embedded stains may redevelop after cleaning, requiring further applications.

Cleanup

Brush-out brooms and wipe down dustpans with a damp cloth. High-pressure air may also be used to remove dust residues from brooms, brushes and dustpans.

SAFETY INFORMATION

Stand Off® Oil & Grease Stain Remover is a thickened silica/surfactant blend. Use appropriate safety equipment and job site controls during application. Read full label and MSDS for precautionary instructions before use. Keep out of the reach of children.

First Aid

Ingestion: Do not induce vomiting. If conscious, give large amounts of water and call a physician, emergency room or poison control center immediately.

Eye Contact: Rinse thoroughly for 15 minutes. Get medical attention.

Skin Contact: Rinse thoroughly. Get medical attention if irritation persists.

Inhalation: Remove to fresh air. Get medical attention as necessary.

24-Hour Emergency Information: INFOTRAC at 800-535-5053

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects.

Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied,

including without limitation the implied warranties of merchantability or fitness for particular purpose. The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environmental and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the Stand Off[®] representative in your area.