

Sentinel **747**

FRESH SCENT MASTIC REMOVER

- **Faster Acting**
- **Biodegradable**
- **Fresh Scent**
- **Greater Coverage Rates**



SENTINEL® 747™ Fresh Scent Mastic Remover is designed to remove asphalt and solvent based mastics commonly found under asbestos containing VAT and VCT floor tile. When sub-floors are rinsed and allowed to dry, new flooring may be installed. This product does not contain asbestos.

SPECIFICATIONS

| | | | |
|----------------------------|------------------|------------------------------|-----------------------|
| APPEARANCE..... | BLUE | ODOR..... | FRESH SCENT |
| APPROX. BOILING POINT..... | 370-518° F. | SPECIFIC GRAVITY (TEMP)..... | (60° F) 806 |
| VAPOR DENSITY..... | HEAVIER THAN AIR | FLASHPOINT..... | 146° F PMCC/ 154° COC |

DIRECTIONS

Floor Tile Mastic Removal:

Step One: If necessary, protect walls, drains, cracks and other flooring with an absorbent (rags, kitty litter, sawdust) to keep liquefied mastic contained.

Step Two: Wet the entire adhesive surface with 747™. This may be done by using a sprayer or by mopping 747™ over the surface of the mastic. Allow 747™ to soak and penetrate for 10-20 minutes to saturate the mastic.

Step Three: Scrape or squeegee the bulk of the softened or liquefied mastic from the surface with a floor scraper (razor scraper) or floor squeegee.

Step Four: Wash and rinse the floor thoroughly with Sentinel 805 and water to ensure a clean surface. Allow to dry a minimum of 24 hours before installing new flooring.

Coverage for the mastic remover will range from 100-200 square feet per gallon.

For additional information, contact Sentinel's Customer Service at 800-373-0633 or on the web at www.senpro.com

51 NE 77th Ave
Mpls, MN 55432



800-373-0633
Fax 763-571-1819