



**PRODUCTS**

Division of Sierra Corporation

# TRI-GRIP- Non-Slip Synthetic Aggregate

Meets Federal EPA's VOC Requirements

## Technical Data

### 1. PRODUCT NAME:

TRI-GRIP- Non-Slip Synthetic Aggregate

### 2. MANUFACTURER

TK PRODUCTS, DIVISION  
OF SIERRA CORPORATION  
11400 West 47th Street  
Minnetonka, MN 55343  
952-938-7223  
952-938-8084 (FAX)  
E-mail: tkproduct@AOL.com  
Website: <http://www.tkproduct.com>

### 3. PRODUCT DESCRIPTION:

TRI-GRIP -a Non-Slip Synthetic Aggregate is made up of Polypropylene sphere shaped particles. The advantage is it creates a textured surface without sharp edges. They are lightweight so they will stay suspended in TK Products' curing and sealing compounds easily. They are clear, so unnoticeable on the floor. Can be used in TK Products' Cure & Seals and TK Products' Colored Stains.

### USES:

Use on commercial floors near entrance doors, garage floors, driveways, patios, steps or any concrete surface you want a texture added to the surface.

### 4. TECHNICAL DATA

Tri-grip is polypropylene in small sphere shaped particles.

This product is currently not regulated by 1999 Federal EPA VOC Requirements.

### 5. APPLICATION PROCEDURES AND INSTRUCTIONS

Tri-Grip comes in a 1# Containers. Add Tri-Grip aggregate to 5 gallons of Cure &

Seal. You can add two containers of Tri-Grip or one-half container into 5 gallons of Cure & Seal to get more or less texture. Tri-Grip can be added to the Cure & Seal 12 hours before application. Shake or stir container before application to bring the aggregate back up in suspension. Shake or stir while using to keep the aggregate in suspension. It can be brushed, rolled, or sprayed to concrete surfaces. (If sprayed use large tip size as used for white pigmented sealers.)

Cure & Seal with Tri-Grip can be applied in more than one coat.

Tri-Grip gives a light texture to the floor so a Cure & Seal without Tri-Grip should not be applied over it for it will take away the texture.

### Preparation:

Clean the concrete floor of any dirt, oil or other contaminates. Use TK-101 Chemical Cleaner or other suitable cleaner for removing grease or oil stains. Rinse well, and let the concrete floor dry.

### Mixing:

Add 1 pound of Tri-Grip to 5 gallons of Cure & Seal for standard texture. More or less Tri-Grip used will result in different textures.

### Coverage:

200 to 400 sq. ft. per gallon.

### Maintenance:

Tri-Grip is a synthetic resin and is subject to wear. Areas of the

concrete floor that show signs of wear can be recoated to bring back the texture.

### 6. AVAILABILITY

TRI-GRIP is packaged in 1# Containers- enough for 5 gallons of Cure & Seal.

### 7. LIMITED WARRANTY

TK Products, a division of The Sierra Corporation, warrants that its products conform to their label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of its products by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. SHOULD ANY OF ITS PRODUCTS FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCTS OR, AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF THE PRODUCTS OF TK PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing. See also TK PRODUCTS DISCLAIMER section below.

### 8. TECHNICAL SERVICES

The TK office offers assistance with specifications, performance test data and field services.

### 9. FILING SYSTEMS

Information Handling Services  
PO BOX 1213  
Englewood, CO 80150  
Information Marketing Services  
13271 Northend  
Oak Park, MI 48237

TRI-GRIP  
Non-Slip Synthetic Aggregate

PRODUCTS  
3



PRODUCTS  
3

TRI-GRIP  
Non-Slip Synthetic Aggregate

**TK DISCLAIMER:**

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also LIMITED WARRANTY (Section 7) above.

**FOR INDUSTRIAL USE ONLY**