

# TK-2012

## KWIK KLEAN

### BIODEGRADABLE CLEANER

Color	CLEAR	
Packaging	1 QUART, 1 GALLON, 5 GALLON AND 55 GALLON CONTAINERS	
Vehicle Type	N/A	
Solvent Type	ESTERS AND KETONES	
Gloss at 60° Angle	N/A	
% Solids by Weight	N/A	
Viscosity at 77° F	15 - 20 SECONDS ZAHN #2	
Desired Dry Film	MAINTAIN OPEN FILM	
Recommended Coverage Rate*	200 TO 300 SQUARE FEET PER GALLON	
Average Dry Time at 70° F	Tack Free	N/A
	Recoat	N/A
	Full Cure	N/A
Catalyst	NOT REQUIRED	
Thinner	NONE	
Mix Ratio	N/A	
Pot Life	OPEN	
Recommended Primer	Steel	N/A
	Galvanized	N/A
	Concrete	N/A
Flash Point	115 ° F	
V.O.C.	5.32 POUNDS PER GALLON	
A.I.M. Category V.O.C. Limit	NOT REGULATED	

\*Coverage: Theoretical coverage rates are a laboratory calculation based on the solids content and the desired dry film thickness. It does not take into consideration substrate porosity, application procedures, weather conditions, over-spray, and wind loss.

It is always advisable to apply a test panel or mock-up prior to the project start-up. This will help to determine proper coverage, appearance, and equipment requirements.

**General Description:**

TK-2012 KWIK-KLEAN BIO-DEGRADABLE CLEANER IS DESIGNED TO REMOVE ACRYLIC RESIN BASED CURING AND SEALING COMPOUNDS, AS WELL AS MOST FORMS OF GRAFFITI FROM CONCRETE SURFACES. IN ADDITION, TK-2012 KWIK-KLEAN WILL ALSO SUCCESSFULLY REMOVE MOST CARPET AND VINYL FLOOR ADHESIVES AND MANY FORMS OF PAINT (I.E. DRY FOGS, LATEX, ACRYLICS, ETC.) FROM CONCRETE SURFACES BOTH VERTICAL AND HORIZONTAL. TK-2012 KWIK KLEAN MAY ALSO BE USED AS A STAIN AND DIRT REMOVER FROM CONCRETE FLOORS AND DRIVEWAYS.

**Resistance to:**

Abrasion	N/A
Acid	N/A
Alkali	N/A
Humidity	N/A
Petroleum Products	N/A
Salt Spray	N/A
Weather	N/A

**Mixing Detail:**

STIR OR SHAKE BEFORE USING.

**Surface Preparation:**

SURFACE MUST BE DRY. IF EXTREMELY CONTAMINATED WITH DIRT, MUD ETC., POWER WASH AND ALLOW TO DRY BEFORE USING KWIK KLEAN.

**Application Procedure:**

APPLY TK-2012 KWIK KLEAN BY SPRAY, BRUSH OR ROLLER AT A RATE OF 200-300 FT<sup>2</sup>/GALLON. KWIK KLEAN IS MOST EFFECTIVE WHEN FLOODED ON KEEPING THE SURFACE WET FOR 5-10 MINUTES. IF STAIN HAS NOT STARTED TO DISSOLVE OR RUN OFF THE SURFACE, REAPPLY AND USE A STIFF BRISTLE BRUSH OR BROOM TO AID IN REMOVAL. WIPE CLEAN WITH CLOTH AND RINSE AREA WITH CLEAN WATER. TO AVOID SPONTANEOUS COMBUSTION DURING TEMPORARY STORAGE, SOAK SOILED RAGS AND WASTE IMMEDIATELY AFTER USE IN WATER FILLED, CLOSED METAL CONTAINER. TO REMOVE CURING AND SEALING COMPOUNDS, APPLY TO SURFACE FOR 15-30 MINUTES. TK-2012 MAY THEN BE REMOVED BY SCRAPER, AND PLACING RESIDUE INTO A CLOSED METAL CONTAINER TO AVOID SPONTANEOUS COMBUSTION. SURFACE SHOULD THEN BE PRESSURE WASHED TO REMOVE ANY REMAINING RESIDUE AND CONTAMINATION.

**Clean Up:**

USE WARM SOAPY WATER IMMEDIATELY.

**Safety Information:**

INHALATION: EXCESSIVE AND PROLONGED INHALATION MAY RESULT IN HEADACHE, NAUSEA, AND EYE AND LUNG IRRITATION. INGESTION HEALTH RISKS AND SYMPTOMS: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. HEALTH HAZARDS: OVER EXPOSURE OF THIS MATERIAL HAS BEEN SUGGESTED AS A CAUSE OF CARDIAC ABNORMALITIES. IF SPILLED: ELIMINATED ALL SOURCES OF IGNITION, FLARES, FLAMES, INCLUDING PILOT LIGHTS. STOP SPILL AT SOURCE. TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT. PRECAUTIONS: KEEP AWAY FROM FIRE, SPARKS OR FLAMES AS RESIDUAL VAPORS AND RESIDUE. DO NOT CUT, PUNCTURE, OR WELD ON OR NEAR THIS CONTAINER FOR ANY PURPOSE UNTIL COMMERCIALY CLEANED. RESPIRATORY PROTECTION: IF EXPOSURE LIMITS OF PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENSE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS.

FOR FURTHER INFORMATION SEE MSDS

**HMIS:**

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	G

**Conditions of Sale:**

TK Products, division of The Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT OR, AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.