



Tyvek[®]
CommercialWrap[®]



Tyvek[®]
CommercialWrap[®]



Tyvek[®]
CommercialWrap[®]

Product Specifications for Tyvek[®] CommercialWrap[®]

PROPERTIES	METHOD	TYVEK [®] COMMERCIALWRAP [®]
Air Penetration	Air-Ins (cfm/ft ² @75 Pa)	.001
	Gurley Hill (TAPPI T-460) (sec/100cc)	>1500
	ASTM E-1677	Type 1
Water Vapor Transmission	ASTM E-96 Method B (g/m ² -24 hrs) (perms)	200 28
	Water Penetration Resistance	AATCC-127 (cm)
Basis Weight	TAPPI T-41D (oz/yd ²)	2.7
Breaking Strength	ASTM D-882 Method A (lbs/in)	38/35
Tear Resistance (trapezoid)	ASTM D-1117 (lbs)	12/10
Surface Burning Characteristics	ASTM E-84-97a Flame Spread	Class A
	Indexed Smoke Developed Value	Class A

WARNING: Tyvek[®] is combustible and should be protected from a flame and other high heat sources. If the temperature of Tyvek[®] reaches 750 F (400 C), it will burn and the fire may spread and fall away from the point of ignition.

For more information:

1-800-44-TYVEK[®]
www.tyvekconstruction.com




Tyvek[®] CommercialWrap[®]

Build it once, build it right.