

DuPont™ Flashing Tape

PHYSICAL PROPERTIES DATA SHEET

Product Data

PROPERTIES	DUPONT™ FLASHING TAPE
Face Sheet	Polypropylene film
Adhesive	Butyl rubber (black)
Thickness	20 mil (507 microns)
Release Liner	1-piece heavy-duty siliconized paper
Dimensions	4-, 6- or 9-inch width x 100 feet
Applications	Jams and heads of rectangular windows.

Performance Testing

MEETS AAMA 711-07 MATERIAL STANDARD FOR SELF-ADHERED FLASHING PRODUCTS

Adhesion Class Rating	Class A (no need for primer under tested conditions)
Thermal Exposure	Level 3 - Highest level (176 °F/80 °C at 7 days)
Installation	Can be installed at external temperatures as low as 25 °F (-4 °C)

INSTALLED SYSTEM WATER INTRUSION TESTING

(Tested with no exterior cladding)

ASTM E331	No leakage at 300 Pa
-----------	----------------------

WATER VAPOR PERMEABILITY (ASTM E96)	< 1 perm (< 60 ng/Pa.sec.m ²)
-------------------------------------	---

APPLICATION TEMPERATURE	Best when installed above 25 °F (consult DuPont for primer recommendations)
-------------------------	---

UV RESISTANCE	Cover within 120 days
---------------	-----------------------

For more information about DuPont™ Weatherization Systems, please call 1-800-44-Tyvek or visit us at www.Construction.Tyvek.com

WARNING: DuPont™ Flashing Tape with its release paper intact is slippery and therefore poses a potential safety hazard if walked on. Discard removed release paper in such a way as to avoid a potential slipping hazard.

DuPont™ Flashing Tape is combustible and should not be exposed to an open flame or other ignition sources.



The miracles of science™

DuPont™
Flashing Tape