



Williams Products, Inc

1750 Maplelawn

Troy, MI. 48084

Toll Free: 800-521-9594 Phone: 248-643-6400

Fax: 248-643-7117

Everlastic® 1320 Series Polyurethane Foam

Description:

2PD Open Cell Polyurethane Foam 1320 Series

Uses:

Rectangular Backer Material to Receive Sealant/Fill Joint, Ceiling Tile Bedding (Dust Shield)

Available Sizes:

1/8" thru 4" thickness, Also Available in rolls (Standard Sheet Size 54" x 96"), Available with pressure sensitive temporary adhesive.

Typical Physical Properties:

Property	Typical Values
Density	2.0 lb./ft ³
Compression Deflection (un-aged) 25%	0.65 lb./in ²
Compression Deflection (un-aged) 50%	0.75 lb./in
Compression Deflection (un-aged) 70%	1.4 lb./in
Tensile Strength	2.0 lb./ft ³
Tensile Elongation	170 %
Tear Resistance	2.0 lb./in
50% Compression Set	2.0 lb./in
Dry Heat Aging (24 hrs @ 140°C)	80 % Retention of Tensile Strength
Clickability	Excellent
U.L 94 HF - 1 (aged)	Pass
Steam Autoclave	70 % Retention of Tensile Strength



We do not guarantee the applicability or accuracy of this information or the suitability of our products for any given situation. The products discussed are sold without warranty, expressed or implied. Buyer assumes all responsibility for any loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.