

BUILDING AND REINFORCING FABRIC

Northwestern building and reinforcing fabrics combat shrinkage while concrete is curing, and later prevent cracks or spreading resulting from foundation settling, weather extremes or load stress. Wires are rigidly welded. Gauge, mesh size and steel grade meet all A. S. T. M. specifications. Wires are cut flush top and bottom for easier handling.

Building Fabric—60" x 150' Rolls

Spacing	Gauge	Approx. Wt. Per 100 Sq. Feet
6 x 6	10/10	21.0
6 x 6	8/8	30.0
6 x 6	6/6	42.0
6 x 6	4/4	58.0
*6 x 6	3/3	68.0
*6 x 6	2/2	78.0
*6 x 6	1/1	91.0
*6 x 6	0/0	107.0
†4 x 4	10/10	31.0
†4 x 4	8/8	44.0
4 x 4	6/6	62.0
4 x 4	4/4	85.0

*Flat Sheets Only

†Rolls Only

Galvanized Burial Vault Fabric— 28" x 300' Rolls

Style	Approx. Wt. Per 100 Sq. Feet
2 1/2 x 2 x 16	12.0

Galvanized Welded Reinforcing Fabric—60" x 150' Rolls

Style	Approx. Wt. Per 100 Sq. Feet
2 x 2 x 16	13.0
2 x 2 x 14	21.0
4 x 4 x 14	11.0

