



EUCLID CHEMICAL

# EUCO SOLVENT

## CLEAN-UP AND FLOOR STRIPPER PRODUCT

### DESCRIPTION

**EUCO SOLVENT** is a high-strength solvent for numerous uses from tool clean-up to cure & seal membrane removal. It is a pure liquid and contains no added fillers or solids.

### PRIMARY APPLICATIONS

- Cleaning of tools and equipment
- Removal of resin based curing membranes and sealers from floor surfaces
- Removal of blotchiness and whitening issues with acrylic sealers, caused by over-application and/or moisture build up under the sealer
- Breakdown of oil, grease and tar build-up
- Clean-up of epoxy equipment and tools
- Troweling aid for epoxy mortars

### FEATURES/BENEFITS

- High strength for fast clean-up
- Multiple components for maximum effectiveness
- Helps re-wet acrylic sealers to fix aesthetic problems caused by over-application and/or moisture build up

### TECHNICAL INFORMATION

**Appearance:** EUCO SOLVENT is a clear, low viscosity liquid.

### PACKAGING

EUCO SOLVENT is packaged in 5 gal (18.9 L) pails and in cases of 1 gal (3.8 L) jugs (4 jugs per case).

### SHELF LIFE

2 years in original, unopened containers

### COVERAGE

**Floor Stripping:** For solvent based curing compound removal, an application rate of 100 ft<sup>2</sup>/gal (2.45 m<sup>2</sup>/L) will remove most of the sealer. (This product may not be effective in removing some water based curing and sealing products.) Cured epoxy sealers and coatings may require 2 to 3 applications for complete removal.

### DIRECTIONS FOR USE

**Surface Preparation:** Cleaning or curing compound/sealer removal is easiest if the material has not hardened.

**Mixing:** EUCO SOLVENT requires no premixing. The product is ready for use directly from the container.

**Placement:** Apply EUCO SOLVENT directly on the area to be cleaned or stripped. Keep the area wet and allow to soften for 5 to 10 minutes. Reapply additional solvent and begin resin removal by scraping or scrubbing with a solvent-resistant brush. When performing a solvent wash on surfaces coated with acrylic sealers, keep the area wet and allow to soften for 5 to 10 minutes. Re-apply additional solvent and begin sealer re-distribution and/or removal using a combination of scrubbing with a solvent-resistant brush and back rolling with a solvent-resistant roller.

### CLEAN-UP

Clean tools with brushes before resin residue has hardened. If the resin has hardened, submerge the tools in EUCO SOLVENT until the residue has softened and can be scraped away.

MISCELLANEOUS

EUCO SOLVENT

 MASTER FORMAT #:  
03 01 30.51

## PRECAUTIONS/LIMITATIONS

---

- Do not use near sparks or open flames.
- Use only in well ventilated areas.
- If HVAC intake ducts will distribute solvent odor into adjoining occupied areas of the building, care should be taken to block these ventilation vents.
- Always wear protective clothing (rubber gloves, eye protections, etc).
- Use EUCO CLEAN & STRIP whenever solvent odor is unacceptable.
- In all cases, consult the Safety Data Sheet before use.

Rev. 02.19

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.